

# ELASTO-Clean AP

## Cleaning and rinsing agent for PU-plastic systems

ELASTO-Clean AP is a cleaner based on specially modified esters. It was developed for rinsing and cleaning of plastic dosing systems and production vessels. ELASTO-Clean AP acts outstandingly on polyurethane.

Technical Data	
Density (g/cm <sup>3</sup> ) at 20 °C	0,92
Surface Tension (mN/m) at 25 °C	< 40
Boiling range (°C)	> 145
Flash point (°C)	42
pH-value (10 g / l H <sub>2</sub> O)	not determined
Vapor pressure (mbar) at 20 °C	> 1
Application temperature (°C)	room temperature
Self ignition (°C)	> 200
Solubility in water (%)	not miscible or difficult to mix
Application concentration (%)	100
Biological degradation	yes

Application Areas			
Removes:			
Polyurethane (PUR)	++	Polyolefin (APAO)	-
Epoxy (EP)	+	Glues / Adhesives	+
Polyester (P)	+	Paints / Coatings	+
Oil + Fat	+	General dirt	+

Processes			
Dip cleaning	++	Spray in air	o
Ultrasonic	++	Manual by hand	++
<div> <div>++ very recommended</div> <div>+ recommended</div> <div>o possible, but not recommended</div> <div>- not recommended</div> </div>			

General information
Free of halogenated and aromatic compounds
Dangerous goods
No VOC tax (Switzerland)
Shelf life in sealed containers: > 3 years
Free of water and surfactants
No general corrosive effect on standart base materials
High bath loading capacity = long life
Product will be sent as ready-to-use solution.



ISO 9001 / ISO 14001