

RESIN-Clean VF-610

Remover for 1k- and 2k-plastic systems and adhesives

RESIN-Clean VF-610 is a modified cleaning agent designed to remove different and even persistent plastic and adhesives residues from most metallic substrates. This product owns strong cleaning capacities.

Technical Data	
Density (g/cm ³) at 20 °C	1,05 – 1,10
Surface tension (mN/m) at 25 °C	< 40
Boiling range (°C)	> 190
Flash point (°C)	95
pH-value (10 g / l H ₂ O)	n.a.
Vapor pressure (mbar) at 20 °C	2,5
Application temperature (°C)	20 - 75
Self ignition (°C)	200
Solubility in water (%)	Not miscible or difficult to mix
Application concentration (%)	100
Biodegradability	yes

Application Areas			
Removes:			
Polyurethans (PUR)	++	Polyolephins (APAO)	o
Epoxy (EP)	+	Adhesives	+
Polyesters (P)	+	Paints + Laquers	+
Oils + Greases	o	General dirt	+

Processes			
Dip cleaning	++	Spray in air	++
Ultrasonic	++	Manual by hand	o

++ very recommended	+ recommended	o possible, but not recommended	– not recommended
---------------------	---------------	---------------------------------	-------------------

General Information
Free of halogenated and aromatic compounds
No dangerous goods
No VOC-tax (Switzerland)
Shelf life in sealed containers: > 3 years
Free of water and surfactants
No general corrosive effect on standard base materials
High bath loading capacity = long life
Product will be sent as ready-to use solution.
RESIN-Clean VF-610 is also available in paste form named RESIN-Clean VF-610/P.



ISO 9001 / ISO 14001