

UNI-Clean 10/VF

High efficiency cleaner for fat and oil
Substitute for acetone, methyl ethyl ketone and thinner

UNI-Clean 10/VF is a cleaner based on high-purity hydrocarbons. It dries very quickly on surfaces and leaves no residues.

Technical Data	
Density (g/cm ³) at 20 °C	0,68
Surface tension (mN/m) at 25 °C	< 30
Boiling range (°C)	98
Flash point (°C)	< 0
pH-value (10 g / l H ₂ O)	n.a.
Vapor pressure (mbar) at 20 °C	48
Application temperature (°C)	25
Self ignition (°C)	> 200
Solubility in water (%)	0
Application concentration (%)	100
Biodegradability	yes

Application Areas			
Removes:			
Polishing paste	++	Plastics	-
Coolant	o	Glues / Adhesives	-
Mold release agent	+	Paints / Coatings	-
Oil + Fat	++	General dirt	++

Processes			
Dip cleaning	++	Spray in air	o
Ultrasonic	++	Manual by hand	++

++ very recommended	+ recommended	o possible, but not recommended	- not recommended
---------------------	---------------	---------------------------------	-------------------

General information
Free of halogenated and aromatic compounds
Dangerous goods
Shelf life in sealed containers: > 3 years
Free of water and surfactants
No general corrosive effect on standart base materials
Excellent degreasing power
Product will be sent as ready-to-use solution.



ISO 9001 / ISO 14001