

# UNI-Clean 350

High efficiency cleaner for fat and oil

UNI-Clean 350 is a cleaner based on high-purity hydrocarbons. It is suitable for all metallic surfaces. Due to the extremely slow drying, the cleaner leaves a light film on the surface, which causes short-term corrosion protection.

| Technical Data                        |                |
|---------------------------------------|----------------|
| Density (g/cm <sup>3</sup> ) at 20 °C | 0,75 – 0,80    |
| Surface tension (mN/m) at 25 °C       | < 40           |
| Boiling range (°C)                    | > 240          |
| Flash point (°C)                      | 105            |
| pH-value (10 g / l H <sub>2</sub> O)  | not applicable |
| Vapor pressure (mbar) at 20 °C        | < 1,0          |
| Application temperature (°C)          | 20-75          |
| Self ignition (°C)                    | > 200          |
| Solubility in water (%)               | not soluble    |
| Application concentration (%)         | 100            |
| Biodegradability                      | yes            |

| Application Areas  |    |                   |    |
|--------------------|----|-------------------|----|
| Removes:           |    |                   |    |
| Polishing paste    | +  | Plastics          | -  |
| Coolant            | o  | Glues / Adhesives | -  |
| Mold release agent | +  | Paints / Coatings | -  |
| Oil + Fat          | ++ | General dirt      | ++ |

| Processes  |    |                |    |
|--|----|----------------|----|
| Dip cleaning   | ++ | Spray in air   | ++ |
| Ultrasonic   | ++ | Manual by hand | ++ |
| <div> <div>++ very recommended</div> <div>+ recommended</div> <div>o possible, but not recommended</div> <div>- not recommended</div> </div> |    |                |    |

| General information                                    |
|--|
| Free of halogenated and aromatic compounds             |
| No dangerous goods                                     |
| Shelf life in sealed containers: > 3 years             |
| Free of water and emulsifiers                          |
| No general corrosive effect on standard base materials |
| Very good degreasing power                             |
| Product will be sent as ready-to-use solution.         |
| Nearly odorless  |



ISO 9001 / ISO 14001