

RESIN-Clean SEC-1

Cleaner for resin and plastic systems

RESIN-Clean SEC-1 is a cleaner based on specific ethers. Resin and plastic impurities can be removed efficiently with RESIN-Clean SEC-1. The product can be used for cleaning tools, machinery and other metal parts. This special product is safe according to its application, the environment and the workplace situation.

Technical Data		
Density (g/cm³) at 20°C	1,0	
Surface tension (mN/m) at 25°C	< 40	
Boiling range (°C)	200	
Flash point (°C)	90	
pH-value (10 g / I H ₂ O)	neutral	
Vapor pressure (mbar) at 20°C	< 1	
Application temperature (°C)	20 - 75	
Self ignition (°C)	> 200	
Solubility in water (%)	100	
Application concentration (%)	100	
Biodegradability	yes	

Application Areas			
Removes:			
Polyurethans (PUR)	++	Polyolephins (APAO)	-
Epoxys (EP)	+	Adhesives	+
Polyesters (P)	++	Paints + Laquers	+
Oils + Greases	++	General dirt	+

Processes			
Dip cleaning	++	Spray in air	+
Ultrasonic	++	Manual by hand	+

++ very	+ recommended	o possible, but not	 not recommended
recommended		recommended	

General Information	
Free of halogenated and aromatic compounds	
No dangerous goods	
Not classified according to the CLP-Regulation	
No VOC-tax (Switzerland)	
No TLV value	
Shelf life in sealed containers: > 3 years	
Free of water and surfactants	
No general corrosive effect on standard base materials	
High bath loading capacity = long life = high efficiency	
Product will be sent as ready-to use solution.	



Färber & Schmid AG Industriestrasse 10 CH-8197 Rafz Telefon +41 (0) 43 322 40 40 fs@faerber-schmid.ch www.faerber-schmid.ch