



Färber & Schmid
Chemie · Technik

DE-Paint XR-16/2

Paint remover/ cleaner

DE-Paint XR-16/2 is a user – and environment friendly organic paint remover. It has specially been designed to remove persistent and cured pollutions of paints, lacquers and dispersions. This cleaner has a high solvency power and is primarily used in automatic washing equipments.

Technical Data	
Density (g/cm ³) at 20 °C	0,90 – 0,95
Surface tension (mN/m) at 25 °C	< 40
Boiling range (°C)	170 - 200
Flash point (°C)	approx. 67
pH-value (10 g / l H ₂ O)	neutral
Vapor pressure (mbar) at 20 °C	ca. 1
Application temperature (°C)	25 - 55
Self ignition (°C)	> 210
Solubility in water (%)	yes
Application concentration (%)	100
Biodegradability	yes

Application Areas			
Removes:			
solvent based coatings	++	water based dispersions	+ (++)

Processes			
Dip cleaning	++	Spray in air	++
Ultrasonic	++	Brushing	++

++ very recommended	+ recommended	o possible, but not recommended	- not recommended
---------------------	---------------	---------------------------------	-------------------

General information
Low foaming
Distillable
Compatible with steel and aluminum
Shelf life in closed containers: 2 years

