

# DE-Paint XR-20/2-M

## Paint remover/ cleaner

DE-Paint XR-20/2-M is a user – and environment friendly paint remover. It has been designed to remove paints and lacquers based on solvent- or water based formulations. This cleaner has a high solvency power and is primarily used in automatic washing equipments.

Technical Data	
Density (g/cm <sup>3</sup> ) at 20 °C	0,95 – 1,00
Surface tension (mN/m) at 25 °C	< 40
Boiling range (°C)	185 - 205
Flash point (°C)	84
pH-value (10 g / l H <sub>2</sub> O)	10,0 – 11,5
Vapor pressure (mbar) at 20 °C	< 2,5
Application temperature (°C)	25 – 70
Self ignition (°C)	> 200
Solubility in water (%)	fully miscible
Application concentration (%)	100
Biodegradability	yes

Application Areas			
Removes:			
Solvent based coatings	++	Water based coatings	++

Processes			
Dip cleaning	++	Spray in air	++
Ultrasonic	++	Brushing	++

++ very recommended	+ recommended	o possible, but not recommended	– not recommended
---------------------	---------------	---------------------------------	-------------------

General information	
Low foaming	
Distillable	
Compatible with steel and aluminum	
VOC tax (Switzerland)	
Free of surfactants and corrosion inhibitors	
Shelf life in closed containers: 2 years	



ISO 9001 / ISO 14001