



Färber & Schmid
Chemie · Technik

DE-Paint XR-25

Paint remover/ cleaner

DE-Paint XR-25 is a user – and environment friendly paint remover. It has been designed to remove paints and lacquers based on solvent- or water based formulations. DE-Paint XR-25 is aprotic and therefore ideal for cleaning 2k-systems such as polyurethane (PU) or epoxy (EP). This cleaner has a high solvency power and is primarily used in automatic washing equipments.

Technical Data	
Density (g/cm ³) at 20 °C	0,90 – 0,95
Surface tension (mN/m) at 25 °C	< 40
Boiling range (°C)	> 150
Flash point (°C)	70
pH-value (10 g / l H ₂ O)	7,5 – 8,5
Vapor pressure (mbar) at 20 °C	> 5
Application temperature (°C)	25 – 55
Self ignition (°C)	approx. 170
Solubility in water (%)	yes
Application concentration (%)	100
Biodegradability	yes

Application Areas			
Removes:			
Solvent based coatings	++	Water based coatings	+ (++)
Polyurethane (PU)	++	Epoxy (EP)	++

Processes			
Dip cleaning	++	Spray in air	++
Ultrasonic	++	Brushing	++

++ very recommended	+ recommended	o possible, but not recommended	– not recommended
---------------------	---------------	---------------------------------	-------------------

General information
Low foaming
Distillable
Compatible with steel and aluminum
No VOC tax (Switzerland)
Shelf life in closed containers: 2 years
No dangerous goods
No classification and labeling according to CLP
No TLV-value
Low-odor



ISO 9001 / ISO 14001

Färber & Schmid AG
Industriestrasse 10
CH-8197 Rafz
Telefon +41 (0) 43 322 40 40
fs@faerber-schmid.ch
www.faelber-schmid.ch